

KDC350 Barcode Data Collector

A New Wave in Auto-ID

The KDC350 enables diverse mobile Auto-Identification applications for collecting and storing barcode data.

A built-in display and keypad eliminate blind erroneous data collection and enable interactive data collection processes.

An easy-to-replace rechargeable battery that can recharge from any USB port allows more than 25,000,000 barcode scans. With 4MB of on-board memory that stores over 100,000 product databases, memory shortages are also no longer a concern.

All KDC products come with FREE KTSync[®] software and SDK. KTSync[®] includes keyboard wedging, application generation, DB look up and inventory management features. SDK provides technical support from our top engineers and development staff.



BlackBerry[®]



Windows




ADVANCED FEATURES

- 1D Laser and 2D Imager Models
- Class2 *Bluetooth*[®] with HID/SPP/MFi (Optional) Profiles
- Bright 1" OLED Display
- 3 or 19 Keypads
- Rechargeable Li-Ion Battery
- 48 Channel GPS Receiver(Optional)/NFC(Optional)
- Stores 100,000+ Product Records
- KTSync[®] with Keyboard Wedging, Application Generation, DB Look up and Inventory Management features.

Solutions

- Retail
- Transportation
- Field Services
- Warehouse
- Healthcare
- Hospitality
- Event Technology



KDC350 Specifications

Hardware Specifications

Physical Characteristics

- **Size** : 1.69" x 3.70" x 0.94"
(43 mm x 94 mm x 24 mm)
- **Weight** : 3.0 oz (85 grams)

Electrical Characteristics

- **Battery** :
KDC350: Lithium-Ion (3.7V DC, 1200mAh) softpack
KDC350R2: Lithium-Ion (3.7V DC, 1130mAh) hardpack
- **Charging** : Via USB connector, Charging cradle
- **Typical Operating Current** : 300mA@3.3V

GPS (Optional)

PT9250 48 channel GPS Receiver

NFC (Optional)

MIFARE Ultralight/Ultralight C/1K, ISO15693

User Environment

- Ingress Protection Rating** : IP65
- Drop Spec**: 5 feet (1.5m)
- Operating** : -4°F (-20°C) ~ 122°F (50°C)
- Storage** : -4°F (-20°C) ~ 140°F (60°C)
- Humidity** : 5% ~ 95% (noncondensing)

Interfaces

Bluetooth® V2.1+EDR, Class 2, HID/SPP/MFi
USB to Serial (Ultra mini USB port)

Keypad

19 Alphanumeric including scan and scroll buttons

Functionality

- Memory Flash ROM** : 256KB Program, 4MB User Data
- Memory RAM** : 64KB
- Microprocessor** : ARM7, 32 bits
- Real-time Clock** : Quartz RTC for timestamp

For more information, contact:

KOAMTAC Inc.

116 Village Blvd. Suite 305
Princeton, NJ 08540, USA

Tel +1-609-256-4700

Fax +1-609-228-4373

E-mail info@KOAMTAC.com

www.KOAMTAC.com

Scan Engine & Symbologies

Scan Engine :

- KDC350 : Option VLM4122(1D), Honeywell 5100
- KDC350R2 : Motorola SE960(1D), Honeywell N5600

Symbologies : All major 1D and 2D Symbologies

Wedging & Synchronization

- Store to a file or transfer to the application
- Keyboard wedge function
- Add-on prefixes and suffixes
- Barcode option selection

Application Generation

- SDK for PC and Smartphone application
- Application generation tool
- Database lookup feature
- Inventory management feature

Regulatory Conformance

Laser Safety – IEC/CDRH Class II

EMC - CE, FCC, KCC, TELEC

Models

KDC350L-OP, KDC350Li-OP, KDC350LN-OP, KDC350Lni-OP, KDC350LG-OP, KDC350Lgi-OP, KDC350LNG-OP, KDC350LNGi-OP, KDC350C-SR/SF, KDC350Ci-SR/SF, KDC350CN-SR/SF, KDC350Cni-SR/SF, KDC350CG-SR/SF, KDC350CGi-SR/SF, DC350CNG-SR/SF, KDC350CNGi-SR/SF, KDC350L-MO-R2, KDC350Li-MO-R2, KDC350Lni-MO-R2, KDC350LNG-MO-R2, KDC350LNGi-MO-R2, KDC350LG-MO-R2, KDC350Lgi-MO-R2, KDC350LNG-MO-R2, KDC350LNGi-MO-R2, KDC350C-G6SR-R2, KDC350C-G6SR-3K-R2, KDC350Ci-G6SR-R2, KDC350Ci-G6SR-3K-R2, KDC350CN-G6SR-R2, KDC350Cni-G6SR-R2, KDC350CG-G6SR-R2, KDC350CGi-G6SR-R2, KDC350CNG-G6SR-R2, KDC350CNGi-G6SR-R2

Package Contents



1 KDC350 1 Lanyard 1 USB cable 1 Software CD
Data Collector

